

## **OVERVIEW**

**FEATURES** 

■ Portable

Only 6.0 lb

■ High Resolution
✓ 10 Pa (0.1 mbar)

■ Great Stability

dirt

■ Easy-to-use

The ADT 916 Pneumatic Pressure Test Pump is a hand operated pressure pump designed to generate pressure from -14psi (-0.95bar) to 600psi (40bar). A high-quality screw press is designed for fine pressure adjustment, with an adjustment resolution up to 10 Pa (0.1 mbar). A specially designed shut-off valve makes the pressure as stable as possible during calibration. A built-in gas-liquid isolator protects the pump from moisture and dirt to reduce the need for maintenance. Two hand-light connectors installed on the pump allow easy connecting and disconnecting to the test pump without the need for PTFE tape or wrenches. The ADT 916 is an ideal comparison test pump for pressure instruments calibration.

High-quality screw press for fine pressure adjustment

A specially designed shut-off valve makes the pressure as

Built-in gas-liquid isolator protects the pump from moisture and

Allows easy connecting and disconnecting to the test pump

without the need for PTFE tape or wrenches.

stable as possible during calibration.

■ Durable and Minimal Maintenance

#### Generate 95% vacuum to 600 psi (40 bar) pressure



- Portable, only 6.0 lb
- · Great stability and high resolution
- Minimal maintenance
- · Hand-tight connectors

## **SPECIFICATIONS**

- Media: Air.
- Generated Pressure Range
- 14 psi (0.95 bar) vacuum to 600 psi (40 bar) positive
- Pressure Resolution: 10 Pa (0.1 mbar).
- Material

Ram/adapters: SST

Body: SST/aluminum

Seals: Buna-N

Connection

Connection

Hand-tight connectors for both test gauge and reference gauge.

Test Gauge Connection: 1/4" NPT female.


Reference Gauge Connection: 1/4" NPT female.

- Dimensions
  - Height: 5.5" (140 mm)
  - Base: 12.4" (315 mm) x 7.8" (198 mm)
- Weight: 6.0 lb (2.7 kg).

#### ORDERING INFORMATION

■ Hand-tight Connectors

■ Model Number



# ■ Optional Accessories

Model number	Description
ADT 103	Adapter and fittings, 1/4* NPT male to various male and female connections.
9904-916	Carrying Case for one ADT916 pump and two ADT681 gauges or ADT672 calibrators
ADT100-HTK-2	Hose Test Kit, 5 feet flexible hose, 8000 psi, 1/4NPT male to 1/2NPT female hand-tight quick connector.
ADT100-HTK-4	Hose Test Kit, 5 feet flexible hose, 8000 psi, 1/4NPT male to 1/4NPT female hand-tight quick connector.